

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-285018

(43)Date of publication of application : 03.10.2002

(51)Int.Cl.

C08L101/10
C08K 5/098
C09J109/00
C09J157/06
C09J171/00
C09J201/10
C09K 3/10

(21)Application number : 2001-088406

(71)Applicant : NITTO KASEI CO LTD

(22)Date of filing : 26.03.2001


(72)Inventor : NAKAMURA HIROMASA
MURANAKA TAKAYUKI
TABUCHI HITOSHI

(54) MOISTURE-CURABLE RESIN COMPOSITION

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a moisture-curable resin composition of which the surface tackiness disappears in a short time as compared with the existing moisture-curable resin composition.

SOLUTION: This moisture-curable resin composition is composed of 100 pts.wt. of an organic polymer (a) containing a silyl group and having at its molecular terminal or on its side chain at least one functional group having a silicon atom bound to a hydrolyzable group per molecule and 0.1-20 pts.wt. of a tin compound (b) of a carboxylic acid which is expressed in general formula (1) below (wherein, R¹, R², R³ are each a 1-10C hydrocarbon group that may be identical or different) where the α carbon atom of the carboxylic acid is a tertiary carbon.



* NOTICES *

JP0 and JP01 are not responsible for any damages caused by the use of this translation.

1. This document has been translated by computer. So the translation may not reflect the original precisely.


2.*** shows the word which can not be translated.

3. In the drawings, any words are not translated.

CLAIMS

[Claim 6a]

[Claim 1] Silyl group content organosilyl polymer (a) 100 weight section which has one basis which has the silicon atom combined with hydroxylo basis, if it will [per molecule] to a molecular terminal or side chain, and a following general formula (1): [Formula 1]



(Among a formula, R¹, R², and R³ are hydrocarbon groups with 1-10 carbon atoms, respectively, and differing, even if R¹, R², and R³ are the same to mutual —***— a moisture curing type resin composition, wherein the carbon atom of the alpha position of carboxylic acid expressed consists of the tin compound (b) 0.1 of the carboxylic acid which is the third class carbon. 2a weight section. [Claim 2] The moisture curing type resin composition according to claim 1, which contains the type resin composition of liquid type resin composition of the agent component (A) containing said silyl group and (b) hydroxyol.

[Claim 3] The moisture curing type resin composition according to claim 1 or 2 in which said silyl group content organosilyl polymer (a) is what uses a polymer of polyether and an ethylene unsaturated compound or a polymer of diene series as a main chain.

[Claim 4] The moisture curing type resin composition according to any one of claims 1 to 3 in which said tin compound (b) is SUTANASU screw phalate or SUTANASU screw neo decanoate.

[Translation done.]

difficult [a use] when it is considered as a hardening resin constituent, 30000 or less are too desirable [a thing] as a number average molecular weight. Although such an organic polymer can be manufactured by a publicly known method, commercial items, such as KANEKA MS polymer by KaneKA Corp., may be used for it.

For the carboxylic acid tin salt expressed with a general formula (1), it is a following general formula (2): [0015]

For the carboxylic acid tin salt expressed with a general formula (1), it is a following general formula (2): [0015]

